

EKR-32/8

Home | Security | Processing | Matrix Switchers

EKR-32/8
32-8 Video/Telemetry Matrix Switcher, 230VAC,

Art-Nr. 75206



Main Features

Up to 32 Inputs / 8 Outputs	Camera Control Selection: Coaxial or RS-485
Multiple Language On-Screen Menu Driven Set-up	Videoloss Detection / VCR Trigger Management
Time/Date/Text Insertion	Video Signal Masking of Fixed Cameras
Group Call-up for Cameras/Monitors	Master / Slave System: 1 Master / 4 Slaves max.
Programmable Camera Sequences incl. Preset Calls	Parallel System: Up to 9 Matrixes can be Connected
Automatic Alarm Call-up	Controllable via 2 different Keyboards

Specifications

Switching	Cross-point matrix
Video inputs (amount)	32
Video inputs loop-through	no
Video inputs	Up to 32x 1.0Vp-p, (C)VBS, 75ohms, BNC
Video outputs (amount)	8
Video outputs	8x 1.0Vp-p, (C)VBS, 75ohms, BNC
Alarm inputs	Up to 32
Alarm outputs	8x Relay contact, 50VAC/0.3A resistive
Alarm display modes	External alarms will call cameras to selected monitors and override the current operational display
Alarm clearance modes	Alarm will be closed either by keyboard acknowledgement, time automatic reset or external reset
Automatic alarm call-up	Up to 32 alarm inputs can be programmed to call any camera or camera salvo to monitor.

EKR-32/8

(Continuation Specifications)

Keyboard	8x keyboards max. via RS-485 interface
Camera control	serial, Control for the functions: fixed or variable speed P/T's, zoom, focus, iris and auxiliaries at suitable equipped camera sites
VCR function control	Head switch pulse
Bandwidth	>6MHz
Signal-to-noise ratio	>47dB at 5.5MHz
Window blanking	privacy zone for fix cameras
Camera sequences	Sequences up to 16 cameras, adjustable dwell time/channel
Menu languages	German, English, Italian, French
On-screen display	Date/time, camera number, alarm status and programmable camera titles.
PC interfaces	RS-232 (matrix setup, loding configuration)
Backup	Set-up and firmware update via RS-232 Interface (Distance of up to 15m max.)
Control Interface	RS-485 (Protocols: Videor, Pelco D, Videotec)
Password protection	programmable
Mounting	Desktop or rack mount
Supply voltage	12VDC
Power consumption	24watts max.
Temperature range (operation)	0°C ~+40°C
Housing	Steel metal
Colour	Pantone Cool Gray 8C
Dimensions (HxWxD)	90x430x180mm
Weight	3.2kg
Parts supplied	19"rack ears, Wide range power supply with power cables (Continent, UK and US standard), RJ-11 cables, RJ-11 shunt box, DB25 Alarm connector, Multilingual manual
Certificates	CE

Optional accessories

75207	EKR-KB1	Universal Keyboard for Matrix Switchers EKR Series, Pantone Coolgray 1C
75212	EKR-PTZFI-R2	RS-232/RS-485/Coax Telemetry Receiver for 230VAC Input and P/T Heads
75209	EKR-PTZFI-R1	RS-232/RS-485 Telemetry Preset Receiver 230VAC, for P/T Heads 24V/230VAC

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

